

Caudron C.R. - 714C1 Propeller & Spinner For Azur 1/32 kit

32003

This is a replacement of too blunt spinner of Azur kit. Also adds some extra details for this part: stiffenings of cutouts for propeller blades and miniature imitations of fasteners are present in our product. More finesse prop blades and hub members are included. Although it will fit good to original kit cowling, you can get the best results by using them along with our “Caudron C.R.-714C1 Front Engine Cowl” (D.O.C. 32002).

Follow attached photos when assembly. Sand-off excess of resin from back of spinner cup and from spinner backplate. Open cutouts for propeller blades. Remove hub sleeves with razor saw, and sand-off excess of material to marked incision. Look at photo for proper position of sleeve on bearing..

A little cleaning-up of propeller blade edge is necessary. Do not remove completely seam line on mounting pins. They will help to get tight fit with hub part. It is recommended to drill small holes on invisible portions of sleeves (again see photo). It will prevent from leaking excess of glue outside. Use 5-minute epoxy for bonding blades with hub. It will left you enough time to adjust correct pitch angle.

Design & Master Pattern by Franek Strzelczyk

High resolution photos at: www.polimedia.pl/apm

Work like with usual resin parts:

Use dust mask to protect respiratory system. Wet sanding is recommended. Avoid contact resin dust with eyes and (prolonged) with skin. May cause irritation or sensitization. Disposable gloves and safety goggles are recommended.

Before painting degrease surface with Testors Plastic-Prep or pure benzine (petroleum ether).

Do not use paint thinner or gasoline. Do not use benzine to degreasing styrene plastic parts.

Prime with good plastic primer (Mr.Hobby: Mr. Resin Primer, Mr.Surfacer 1000), automotive plastic primer or good enamel paint.

Join parts with medium viscosity cyanoacrylate and 5-minute epoxy glue.

Always work in well ventilated area.

Take caution when handling with flammable materials.

